NPAC SMS/Individual Service Provider Certification and Regression Test Plan

For New Entrants Certification and Existing Service Providers/Vendors Regression Testing up to and including NPAC Release 3.4.68

Chapter 15

November June 30, 20136 Release 3.4.68

Table of Contents

1.	NANC 355 – Modification of NPA-NXX Effective Date	4
2.	NANC 408 – SPID Migration Automation Change	12
3.	NANC 414 – Validation of Code Ownership in the NPAC	14
4.	NANC 426 - Provide Modify Request Data to the SOA from Mass Updates	18

15. Individual Turn Up Test Scenarios related to NPAC Release 3.4.0.

Section 15 contains all test cases written for individual Service Provider Turn Up testing of Release 3.4.0.x of the NPAC software.

NANC 355 - Modification of NPA-NXX Effective Date 1.

A. **TEST IDENTITY**

Test Case Number:	NANC 355-1	SUT Priority:	SOA	Required	
			LSMS	N/A	
Objective:	initiated by NPAC P modified and the cur	ersonnel on the NPAC S rent date is less than the ke Subscription Versions	MS where the NPA- existing NPA-NXX	n NPA-NXX modify request NXX Effective Date is Effective Date – Success NXX-Xs/NPBs exist within	

REFERENCES B.

KEIEKEICES				
NANC Change Order Revision Number:	Revision Number: NANC FRS Version		NANC 355	
NANC FRS Version Number:			RR3-658, RR3-659, RR3-661, RR3-662, RR3-663, RR3-665, RR3-668, RR3-671, RR3-672, R3-655,	
NANC IIS Version Number:		Relevant Flow(s):	B.4.1.2 NPA-NXX Modification by NPAC	

C. PREREOUISITE

FREREQUISITE	
Prerequisite Test Cases:	
Prerequisite NPAC Setup:	 The NPA-NXX that is going to be modified in this test case exists on the NPAC SMS, is not involved in an NPA-Split, and does not have any associated subscription versions. Verify the Regional NPA-NXX Modification Flag Indicator is set to TRUE. Verify the Service Provider SOA NPA-NXX Modification Flag Indicator is set to their production value.
Prerequisite SP Setup:	

Row #	NPAC or SP	Test Step	NPAC or SP	Expected Result
1.	NPAC	NPAC personnel take action to modify an NPA-NXX Effective Date for a specified Service Provider: NPAC SMS issues an M-SET request to itself to modify the local serviceProvNPA-NXX object.	NPAC	NPAC SMS receives the M-SET request and issues an M-SET response indicating the serviceProvNPA-NXX object was modified successfully.
2.	NPAC	 Based on the Service Provider SOA NPA-NXX Modification Flag Indicator the NPAC SMS will send: 1. For SP SOAs that are accepting downloads for the NPA-NXX for which the Effective Date was modified: 	SP	 Based on the Service Provider SOA NPA-NXX Modification Flag Indicator setting: 1. All SOAs in the region accepting downloads for the NPA- NXX for which the Effective Date was modified AND that support NPA-NXX Modify, receive the M-SET request serviceProvNPA-NXX in CMIP (or NXMD – NpaNxxModifyDownload in XML).

3.	SP	 The NPAC SMS sends an M-SET request in CMIP (or NXMD – NpaNxxModifyDownload in XML) to all SOAs that support NPA-NXX Modify as indicated in their Service Provider profile, for the NPA-NXX specifying the modified NPA-NXX Effective Date. For SOAs that don't support NPA-NXX Modify as indicated in their Service Provider profile: The NPAC SMS sends an M-DELETE for the serviceProvNPA-NXX object (not available over the XML interface). The SOA responds to the M-DELETE (not available over the XML interface). Then the NPAC SMS sends an M-CREATE for the serviceProvNPA-NXX object (not available over the XML interface). Then the NPAC SMS sends an M-CREATE for the serviceProvNPA-NXX object (not available over the XML interface) (using the same object ID as the DELETE request for the same object) with the modified NPA-NXX Effective Date. Using their SOA, Service Providers perform a local query for the NPA- 	SP	 SOAs that received the M-SET request in CMIP (or NXMD – NpaNxxModifyDownload in XML) issue an M- SET response in CMIP (or DNLR - DownloadReply in XML) indicating the serviceProvNPA-NXX object was modified successfully. 2. All SOAs in the region not accepting downloads for the modified NPA-NXX, receive an M-DELETE for the serviceProvNPA-NXX object (not available over the XML interface) that was modified by NPAC personnel in test step 1, and issue an M-DELETE response (not available over the XML interface) to the NPAC SMS. These same SOAs then receive the M-CREATE for the same serviceProvNPA-NXX object (not available over the XML interface) (including the same object ID indicated in the M-DELETE (not available over the XML interface)). Verify the NPA-NXX exists with the modified NPA-NXX Effective Date. 	
3.	SP		SP		
Е.	Pass/Fa	il Analysis, NANC 355-1			
Pass	Fail	NPAC personnel performed the test c	ase as wr	itten.	
Pass	Fail	Service Provider personnel performed the test case as written and verify the Effective Date for the NPA-NXX in their local system reflects the modified date assigned by NeuStar personnel.			

A. TEST IDENTITY

Test Case Number:	NANC 355-2 SUT Priority:		SOA	N/A
			LSMS	Required
Objective:	NANC 355-2 LSMS - Se request initiated by NPA Date is modified – Succe	C Personnel using the N		

B. REFERENCES

KEFEKEIVCES		
NANC Change Order	Change Order	NANC 355
Revision Number:	Number(s):	
NANC FRS Version	Relevant	RR3-658, RR3-659, RR3-661, RR3-662,
Number:	Requirement (s):	RR3-663, RR3-665, RR3-668, RR3-673,
	-	RR3-674, R3-655
NANC IIS Version	Relevant Flow(s):	B.4.1.2 NPA-NXX Modification by NPAC
Number:		

C. **PREREQUISITE**

Prerequisite Test Cases:	
Prerequisite NPAC Setup:	 The NPA-NXX that is going to be modified in this test case exists on the NPAC SMS, is not involved in an NPA-Split, and does not have any associated subscription versions. Verify the Regional NPA-NXX Modification Flag Indicator is set to TRUE. Verify the Service Provider LSMS NPA-NXX Modification Flag Indicator is set to their production value.
Prerequisite SP Setup:	

Row #	NPAC or SP	Test Step	NPAC or SP	Expected Result
1.	NPAC	NPAC personnel take action to modify an NPA-NXX Effective Date for a specified Service Provider: NPAC SMS issues an M-SET request to itself to modify the local serviceProvNPA-NXX object.	NPAC	NPAC SMS receives the M-SET request and issues an M-SET response indicating the serviceProvNPA-NXX object was modified successfully.
2.	NPAC	 Based on the Service Provider LSMS NPA-NXX Modification Flag Indicator the NPAC SMS will send: 1. For SP LSMSs that are accepting downloads for the NPA-NXX for which the Effective Date was modified: The NPAC SMS sends an M-SET request in CMIP (or NXMD – NpaNxxModifyDownload 	SP	 Based on the Service Provider LSMS NPA-NXX Modification Flag Indicator setting: All LSMSs in the region accepting downloads for the NPA- NXX for which the Effective Date was modified AND that support NPA-NXX Modify, receive the M-SET request serviceProvNPA-NXX in CMIP (or NXMD – NpaNxxModifyDownload in XML). LSMSs that received the M-SET request in CMIP (or NXMD – NpaNxxModifyDownload in XML) issue an M- SET response in CMIP (or DNLR - DownloadReply in XML) indicating the serviceProvNPA-NXX object was modified successfully.

Pass	Fail		rformed the test case as written and verify the Effective Date for the NPA-NXX in modified date assigned by NeuStar personnel.			
Pass	Fail	NPAC personnel performed the test ca				
E.		il Analysis, NANC 355-2				
3.	NPAC	Using their LSMS, Service Providers perform a local query for the NPA-NXX that was modified during this test case.	SP	Verify the NPA-NXX exists with the modified NPA-NXX Effective Date.		
		 in XML) to all LSMSs that support NPA-NXX Modify as indicated in their Service Provider profile, for the NPA-NXX specifying the modified NPA-NXX Effective Date. 2. LSMSs that don't support NPA- NXX Modify as indicated in their Service Provider profile: The NPAC SMS sends an M-DELETE for the serviceProvNPA-NXX object (not available over the XML interface) The LSMS responds (not available over the XML interface) to the M- DELETE. Then the NPAC SMS sends an M-CREATE for the serviceProvNPA-NXX object (not available over the XML interface) (using the same object ID as the DELETE request for the same object) with the modified NPA-NXX Effective Date. 		 All LSMSs in the region not accepting downloads for the modified NPA-NXX, receive an M-DELETE for the serviceProvNPA-NXX object (not available over the XML interface) that was modified by NPAC personnel in test step 1, and issue an M-DELETE response (not available over the XML interface) to the NPAC SMS. These same LSMSs then receive the M-CREATE for the same serviceProvNPA-NXX object (not available over the XML interface) (including the same object ID indicated in the M-DELETE) (not available over the XML interface). 		

A. TEST IDENTITY

Test Case Number:	NANC 355-3	SUT Priority:	SOA	Optional		
			LSMS	N/A		
Objective:	NANC 355-3 SOA – Service Provider Personnel attempt to submit an NPA-NXX modify request to the NPAC SMS – Error					
	Note: Per IIS3_4_1aPart2, this flow is not available over the XML interface (this is NPAC Personnel only functionality).					

B. REFERENCES

NANC Change Order Revision Number:	Change Order Number(s):	NANC 355
NANC FRS Version Number:	Relevant Requirement(s):	RR3-660
NANC IIS Version Number:	Relevant Flow(s):	B.4.1.2 NPA-NXX Modification by NPAC

C. PREREQUISITE

Prerequisite Test Cases:	
Prerequisite NPAC Setup:	 The NPA-NXX that is going to be modified in this test case exists on the NPAC SMS, is not involved in an NPA-Split, and does not have any associated subscription versions. Verify the Regional NPA-NXX Modification Flag Indicator is set to TRUE. Verify the Service Provider LSMS NPA-NXX Modification Flag Indicator is set to their production value.
Prerequisite SP Setup:	

Row #	NPAC or SP	Test Step	NPAC or SP	Expected Result
1.	SP	SP personnel attempt to modify an NPA-NXX Effective Date for an NPA-NXX for whom they are the current SPID. SOA issues an M-SET request in CMIP (not available over the XML interface) to the NPAC SMS for the serviceProvNPA-NXX object specifying a new Effective Date for the NPA-NXX.	NPAC	 NPAC SMS receives an M-SET request in CMIP (not available over the XML interface) for an NPA-NXX to modify the Effective Date. This violates system requirements and the NPAC SMS fails the request. If the Service Provider SOA supports Non-Action Application Level Errors, the NPAC SMS issues an M-SET response processing_failure along with an error code in CMIP (not available over the XML interface). If the Service Provider SOA does not support Non-Action Application Level Errors the NPAC SMS issues an M-SET response indicating access_denied in CMIP (not available over the XML interface). The respective NPA-NXX is not updated.

Е.	Pass/Fai	il Analysis, NANC 355-3
Pass	Fail	NPAC personnel performed the test case as written.
Pass	Fail	Service Provider personnel performed the test case as written and successfully handled the failure from the NPAC SMS.

A. TEST IDENTITY

Test Case Number:	NANC 355-4	SUT Priority:	SOA	N/A
			LSMS	Optional
Objective:	NANC 355-4 LSMS – Service Provider Personnel using their LSMS system attempt to submit an NPA-NXX modify request to the NPAC SMS – Error			
	Note: Per IIS3_4_1aPart2, this flow is not available over the XML interface (this is NPAC Personnel only functionality).			

B. **REFERENCES**

NANC Change Order Revision Number:	Change Order Number(s):	NANC 355
NANC FRS Version Number:	Relevant Requirement(s):	RR3-660
NANC IIS Version Number:	Relevant Flow(s):	B.4.1.2 NPA-NXX Modification by NPAC

C. PREREQUISITE

TREREQUISITE	
Prerequisite Test	
Cases:	
Prerequisite NPAC	1. The NPA-NXX that is going to be modified in this test case exists on the NPAC SMS, is
Setup:	not involved in an NPA-Split, and does not have any associated subscription versions.
	2. Verify the Regional NPA-NXX Modification Flag Indicator is set to TRUE.
	3. Verify the Service Provider LSMS NPA-NXX Modification Flag Indicator is set to their
	production value.
Prerequisite SP	
Setup:	

Row #	NPAC or SP	Test Step	NPAC or SP	Expected Result
1.	SP	SP personnel attempt to modify an NPA-NXX Effective Date for an NPA-NXX for whom they are the current SPID. LSMS issues an M-SET request in CMIP (not available over the XML interface) to the NPAC SMS for the serviceProvNPA-NXX object specifying a new Effective Date for the NPA-NXX.	NPAC	 NPAC SMS receives an M-SET request in CMIP (not available over the XML interface) for an NPA-NXX to modify the Effective Date. This violates system requirements and the NPAC SMS fails the request. If the Service Provider SOA supports Application Level Errors, the NPAC SMS issues an M-SET response processing_failure along with an error code in CMIP. If the Service Provider SOA does not support Application Level Errors the NPAC SMS issues an M-SET response indicating access_denied in CMIP. The respective NPA-NXX is not updated.

Е.	Pass/Fai	il Analysis, NANC 355-4
Pass	Fail	NPAC personnel performed the test case as written.
Pass	Fail	Service Provider personnel performed the test case as written and successfully handled the failure from the NPAC SMS.

2. NANC 408 – SPID Migration Automation Change

A. TEST IDENTITY

Test Case Number:	NANC 408-1	SUT Priority:	SOA	Conditional
			LSMS	Conditional
Objective:	NANC 408 -1 SOA/LSM SPID Migrations, accept of an NPA-NXX.			**

B. **REFERENCES**

NANC Change Order Revision Number:	Change Order Number(s):	NANC 408
NANC FRS Version Number:	Relevant Requirement(s):	RR3-591, RR3-592
NANC IIS Version Number:	Relevant Flow(s):	B.8.5.1 NPAC Initiated SPID Migration Request to Local System

C. **PREREQUISITE**

INEREQUISITE	
Prerequisite Test	
Cases:	
Prerequisite NPAC	1. Verify that the Regional SPID Migration Online Functionality Indicator is set to TRUE.
Setup:	 Verify that the Service Provider SOA Automated SPID Migration Indicator is set to TRUE.
	3. Verify that the Service Provider LSMS Automated SPID Migration Indicator is set to TRUE.
	4. Verify no Pending-Like Subscription Versions or NPA-NXX-Xs/NPBs exist within the respective NPA-NXX(s) indicated in the SPID Migration.
Prerequisite SP Setup:	

Row #	NPAC or SP	Test Step	NPAC or SP	Expected Result
1.	NPAC	NPAC Personnel take action to perform an Online SPID Migration. The NPAC SMS issues an M- ACTION Request InpSpidMigration in CMIP (or SPMN – LnpSpidMigrationNotification in XML) to SOAs and LSMSs in the region that support Automated SPID Migration Indicator (for their respective system).	SP	All SOAs and LSMSs in the region that support Automated SPID Migration receive the M-ACTION Request InpSpidMigration in CMIP (or SPMN – LnpSpidMigrationNotification in XML) from the NPAC SMS and issue an M-ACTION Response InpSpidMigration in CMIP (or NOTR – NotificationReply in XML) back to the NPAC SMS.
2.	SP	SP Personnel perform a local query (using their SOA and/or LSMS) for the NPA-NXX(s) that were updated as a result of the SPID Migration.	SP	Verify the NPA-NXX reflects the code holder as the Migrating To Service Provider in the SPID Migration request.

E.	Pass/Fail Analysis, NANC 408-1	
Pass	Fail	NPAC personnel performed the test case as written.
Pass	Fail	Service Provider personnel performed the test case as written.

3. NANC 414 – Validation of Code Ownership in the NPAC

A. TEST IDENTITY

Test Case Number:	NANC 414 - 1	SUT Priority:	SOA	Optional
			LSMS	N/A
Objective:	NANC 414 -1 SOA – Service Provider personnel using their SOA application submit a NPA NXX create request where the SPID and OCN value as configured on the NPAC SMS do not match the request Error			

B. REFERENCES

NANC Change Order Revision Number:	Change Order Number(s):	NANC 414
NANC FRS Version Number:	Relevant Requirement(s):	R3-687
NANC IIS Version Number:	Relevant Flow(s):	B.4.1.5 NPA-NXX Creation by the SOA

C. PREREQUISITE

PREREQUISITE	
Prerequisite Test	
Cases:	
Prerequisite NPAC	1. Verify the Regional NPAC NPA-NXX Ownership Edit Flag Indicator is set to TRUE.
Setup:	2. Configure a list of valid NPA-NXX for Service Provider under test.
	3. Configure a list of valid OCNs for Service Provider under test.
Prerequisite SP	
Setup:	

D. TEST STEPS and EXPECTED RESULTS

Row #	NPAC or SP	Test Step	NPAC or SP	Expected Result
1.	SP	Service Provider personnel using their SOA take action to create an NPA-NXX for an NPA-NXX where the SPID and the OCN value configured on the NPAC SMS do not match. SOA issues an M-CREATE Request serviceProvNPA-NXX in CMIP (or NXCQ – NpaNxxCreateRequest in XML) to the NPAC SMS.	NPAC	 NPAC receives the M-CREATE Request serviceProvNPA- NXX in CMIP (or NXCQ – NpaNxxCreateRequest in XML) and determines that the SPID and OCN value configured on the NPAC SMS do not match. This violates system requirements. The NPAC SMS logs an error indicating that the NPA-NXX create request failed due to the OCN criteria mismatch. If the Service Provider SOA supports Application Level Errors, the NPAC SMS issues an M-CREATE Error Response in CMIP to the SOA indicating processingFailure along with an error code (or NXCR – NpaNxxCreateReply in XML). If the Service Provider SOA does not support Application Level Errors the NPAC SMS issues an M-SET response in CMIP indicating access_denied (or NXCR – NpaNxxCreateReply in XML). The respective NPA-NXX is not created.

E.

Pass/Fail Analysis, NANC 414-1

Pass	Fail	NPAC personnel performed the test case as written.
Pass	Fail	Service Provider personnel performed the test case as written and handled the failure from the NPAC SMS.

А.	TEST IDENTITY									
	Test Case Number:	NANC 414-2	SUT Priority:	SOA	N/A					
				LSMS	Optional					
	Objective:	NANC 414-2 LSMS – Service Provider personnel using their LSMS application submit a N NXX create request where the SPID and OCN value as configured on the NPAC SMS do no match the request – Error								
		Note: Per IIS3_4_1aPart	t2 scenario B.4.1.4, this t	flow is not available over	Note: Per IIS3_4_1aPart2 scenario B.4.1.4, this flow is not available over the XML interface.					

B. **REFERENCES**

NANC Change Order Revision Number:	Change Order Number(s):	NANC 414
NANC FRS Version Number:	Relevant Requirement(s):	R3-687
NANC IIS Version Number:	Relevant Flow(s):	B.4.1.4 NPA-NXX Creation by the Local SMS

C. PREREQUISITE

TREREQUISITE	
Prerequisite Test Cases:	
Prerequisite NPAC	1. Verify the Regional NPAC NPA-NXX Ownership Edit Flag Indicator is set to TRUE.
Setup:	2. Configure a list of valid NPA-NXX for Service Provider under test.
	3. Configure a list of valid OCNs for Service Provider under test.
Prerequisite SP	
Setup:	

Row #	NPAC or SP	Test Step	NPAC or SP	Expected Result
11.	SP	Service Provider personnel using their LSMS take action to create an NPA-NXX for an NPA-NXX where the SPID and the OCN value configured on the NPAC SMS do not match. LSMS issues an M-CREATE Request serviceProvNPA-NXX to the NPAC SMS.	NPAC	 NPAC receives the M-CREATE Request serviceProvNPA- NXX and determines that the SPID and OCN value configured on the NPAC SMS do not match. This violates system requirements. The NPAC SMS logs an error indicating that the NPA-NXX create request failed due to the OCN criteria mismatch. If the Service Provider LSMS supports Application Level Errors, the NPAC SMS issues an M-CREATE Error Response to the SOA indicating processingFailure along with an error code. If the Service Provider SOA does not support Application Level Errors the NPAC SMS issues an M-SET response indicating access_denied. The respective NPA-NXX is not created.

Е.	Pass/Fai	Pass/Fail Analysis, NANC 414-2		
Pass	Fail	NPAC personnel performed the test case as written.		
Pass	Fail	Service Provider personnel performed the test case as written and handled the failure from the NPAC SMS.		

4. NANC 426 - Provide Modify Request Data to the SOA from Mass Updates

This change order can be certified by executing an updated existing test case from the Turn Up Test Plan.

A. TEST IDENTITY

Test Case Number:	NANC 68 - 1	SUT Priority: SOA		Conditional
			LSMS	Optional
Objective:	NPAC OP GUI – NPAC Personnel submit a Ma Subscription Versions with status of, partial failu within a Service Provider ID and for the TN rang supports Number Pool blocks, the TN range spec Pool Block. – Success		re, sending and disconne e specified). If the Serve	ect-pending exist ice Provider under test

B. REFERENCES

KEI EKEITEED			
NANC Change Order	N/A	Change Order	NANC 68 – Mass Update Requirements
Revision Number:		Number(s):	Modification
NANC FRS Version	2.0.0	Relevant	R3-7.1, R3-7.2, R3-7.5, R3-7.6, R3-7.7
Number:		Requirement(s):	
NANC IIS Version	2.0.1	Relevant Flow(s):	B.8.3 Mass Update
Number:			B.8.3.1 Mass Update for a range of TNs that
			contains a Number Pool Block

C. **PREREQUISITE**

Prerequisite Test	
Cases:	
Prerequisite NPAC	1. Verify that some Subscription Versions exist with a status of active, pending, cancel,
Setup:	cancel-pending, and conflict within the TN range and for the Service Provider you are going to specify in the Mass Update.
	2. Verify no Subscription Versions exist with a status of partial failure, sending, and disconnect-pending.
	3. If the Service Provider under test supports Number pooling, verify a Number Pool Block exist within the TN range specified.
	4. The system under test is configured to receive downloads for the NPA or NPA-NXX used in this test case.
	5. Verify the SOA Supports SV Type and all Optional Data element Indicators are set to their production values for the Service Provider under test. In this test case any Optional Data elements supported by the SP under test and SV Type data (if the SP under test supports it) should be specified.
	6. Verify the Service Provider's S-3.00 C, Attribute Value Change, For Mass update of Active SVs and NPBs notification priority is set to their production value.
Prerequisite SP	
Setup:	

D. TEST STEPS and EXPECTED RESULTS

Row #	NPAC or SP	Test Step	NPAC or SP	Expected Result
1.	NPAC	Using the NPAC OP GUI, NPAC Personnel submit a request for a Mass Update by specifying a TN Range (if the Service Provider under test supports Number Pooling, the TN range should	NPAC	The NPAC SMS searches the Subscription Version database for the Subscription Versions and Number Pool Block (if supported by SUT and indicated in the Mass Update criteria) that match the selection criteria. For all objects that match the criteria, the following occurs:

Release 3.4.<u>68</u>: © 1999-201<u>16, 2013</u> Neustar, Inc.

2.	NPAC	 completely include a Number Pool Block) for a Service Provider ID as the selection criteria. The following attributes will be mass updated (for respective TNs and (if supported by the SUT, Number Pool Block): LRN SV Type – if supported by the Service Provider ISVM DPC ISVM SSN CNAM DPC CNAM SSN LIDB DPC LIDB SSN WSMSC DPC – (if supported by the service provider) WSMSC SSN – (if supported by the service provider Optional Data elements – if supported by the service provider) The NPAC SMS issues: An M-SET subscriptionVersion Request(s) in CMIP (or SVMD – SvModifyDownload in XML) to the LSMS under test to modify the specified attributes for non-pooled SVs in the Mass Update Request. (If the original request criteria included a NPB) The NPAC SMS issues an M-SET in CMIP (or PBMD – NpbModifyDownload in XML) for the number pool block to the LSMSs accepting downloads for this NPA-NXX. 	SP	 The NPAC SMS logs an exception for each Subscription Version within the TN range specified for the Mass Update that has a status of either old, partial failure, sending, cancel or disconnect-pending. If WSMSC data is supported by the LSMS it will be used in the Mass Update. If Optional Data elements or SV Type are supported by the LSMS they will be used in the Mass Update. The LSMS receives: The M-SET Request(s) in CMIP (or SVMD – SvModifyDownload in XML) for the non-pooled SVs. (If the original request criteria included a NPB) The LSMS i receives the M-SET Request numberPoolBlock in CMIP (or PBMD – NpbModifyDownload in XML). The LSMS updates the specified attributes for the Subscription Versions and Number Pool Block (if the original request criteria included a NPB) and issues the respective M-SET Response(s) in CMIP (or DNLR – DownloadReply in XML) back to the NPAC SMS. Only those LSMSs that support WSMSC data and/or Optional Data elements and SV Type will receive that information in the M-SET request.
3.	NPAC	Depending on the Service Provider under test TN Range Notification indicator: The NPAC SMS issues an M- EVENT-REPORT subscriptionVersionStatusAttribute ValueChange in CMIP (or VATN – SvAttributeValueChangeNotificatio n in XML) OR subscriptionVersionRangeStatusAttr ibuteValueChange in CMIP (or VATN –	SP	The Current Service Provider SOA receives the M-EVENT- REPORTs in CMIP (or VATN – SvAttributeValueChangeNotification in XML)/PATN – NpbAttributeValueChangeNotification in XML) from the NPAC SMS and issues M-EVENT-REPORT Confirmations in CMIP (or NOTR – NotificationReply in XML) back to the NPAC SMS indicating it received the NPAC Requests successfully. This includes the subscriptionVersionStatusAttributeValueChange (or RangeStatusAttributeValueChange depending on the TN Range

Release 3.4.<u>68</u>: © 1999-201<u>16, 2013</u> Neustar, Inc.

<u>November June</u> 30, 201<u>36</u>

	SvAttributeValueChangeNotificatio		Notification indicator), as well as the
	n in XML) to the Current Service Provider SOA to set the subscriptionVersionStatus to 'active' for each mass updated (non- pooled) Subscription Version in the range of TNs. The NPAC SMS issues an M- EVENT-REPORT numberPoolBlockStatusAttributeVa lueChange in CMIP (or PATN – NpbAttributeValueChangeNotificati on in XML) to the block holder Service Provider SOA to set the number pool block status to 'active' if the numberPoolBlockSOA- Origination indicator is 'TRUE'.		numberPoolBlockStatusAttributeValueChange (if the numberPoolBlockSOA-Origination indicator is set to TRUE).
4. NPAC	If the Service Provider under test S- 3.00 C, Attribute Value Change, For Mass update of Active SVs and NPBs notification priority is set to a value other than NONE then, depending on their TN Range Notification indicator, The NPAC SMS issues an M-EVENT- REPORT AttributeValueChange in CMIP (or VATN – SvAttributeValueChangeNotificatio n in XML) OR subscriptionVersionRangeAttribute ValueChange in CMIP (or VATN – SvAttributeValueChangeNotificatio n in XML) to the Current Service Provider SOA with the modified attributes for the non-pooled subscription versions. The NPAC SMS would also issue an M-EVENT-REPORT numberPoolBlockAttributeValueCh ange in CMIP (or PATN – NpbAttributeValueChangeNotificati on in XML) to the Current/block holder Service Provider SOA with the modified attributes for the number pool block IF the numberPoolBlockSOA- OriginationIndicator is set to TRUE.	SP	The Current Service Provider SOA receives the M-EVENT- REPORTs in CMIP (or VATN – SvAttributeValueChangeNotification in XML/PATN – NpbAttributeValueChangeNotification in XML) from the NPAC SMS and issues M-EVENT-REPORT Confirmations in CMIP (or NOTR – NotificationReply in XML) back to the NPAC SMS indicating it received the NPAC Request successfully. This includes the subscriptionVersionAttributeValueChange (or RangeAttributeValueChange depending on the TN Range Notification indicator), as well as the numberPoolBlockAttributeValueChange (if the numberPoolBlockSOA-Origination indicator is set to TRUE).
5. NPAC	Using the NPAC OP GUI, request a Mass Update Exception Report by specifying a time range that corresponds to the creation timestamp for the 'exception' log	NPAC	 The NPAC SMS generates a Mass Update exception report to the specified destination, ordered by timestamp, including the following information for the Subscription Versions that were not updated during Mass Update processing: Subscription Version ID
	entries created as a result of the Mass Update requested.		 Subscription Version ID TN Current Service Provider

Release 3.4.<u>68</u>: © 1999-201<u>16, 2013</u> Neustar, Inc.

<u>November June</u> 30, 201<u>36</u>

				 Event ID of the Mass Update Request Timestamp of the Mass Update exception Subscription Version status at the time of exception The report for this test case should not contain exceptions if the Mass Update was processed appropriately.
6.	NPAC	NPAC Personnel perform a query for the Subscription Versions and Number Pool Block in the range that did not have exceptions to verify that the fields selected to be mass updated were modified.	NPAC	The Subscription Versions and Number Pool Blocks were modified correctly.
7.	SP - optional	SP Personnel, using their LSMS, perform a local query for the Subscription Versions and also query for the Number Pool Block to verify that the fields selected to be mass updated were modified.	SP	The Subscription Versions and Number Pool Block were modified correctly. Verify that Active Subscription Versions and the active Number Pool Block that meet the Mass Update criteria are updated.
8.	SP	If the Service Provider under test S- 3.00 C, Attribute Value Change, For Mass update of Active SVs and NPBs notification priority is set to a value other than NONE then SP Personnel using their SOA should perform a local query for the Subscription Versions and Number Pool Block (if the numberPoolBlockSOA-Origination Indicator is TRUE) to verify the fields selected to be mass updated were modified.	SP	The Subscription Version and Number Pool Block (if numberPoolBlockSOA-Origination Indicator is set to TRUE) attributes were modified as specified in the Mass Update request.
9.	SP – conditio nal	SP Personnel, using either the SOA/SOA LTI or LSMS, perform an NPAC query for the Subscription Versions and Number Pool Block in the range that did not have exceptions to verify that the Subscription Version fields selected to be mass updated were modified.	SP	The Subscription Versions and Number Pool Block were modified correctly. Verify that Active Subscription Versions and the active Number Pool Block that meet the Mass Update criteria are updated.
10.	NPAC	NPAC Personnel perform a full audit for the Subscription Version and Number Pool Block that were updated during this test case.	NPAC	Using the Audit Results Log verify that no updates were sent as a result of performing the audit. If updates were issued, the LSMS fails this test case.
Е.	Pass/Fai	il Analysis, NANC 68-1		

		• '
Pass	Fail	NPAC personnel performed the test case as written.
Pass	Fail	Service Provider personnel performed the test case as written and handled the failure from the NPAC SMS.